

SPECIFICHE TECNICHE

Caratteristiche	CPC 8"	CPC 9" 1/4	CPC 11"
Schema ottico	Schmidt-Cassegrain	Schmidt-Cassegrain	Schmidt-Cassegrain
Diametro	203.2 mm	235 mm	280 mm
Focale	2032 mm	2350 mm	2800 mm
Apertura	10	10	10
Cercatore	8x50	8x50	8x50
Montatura	Dual Fork Arm	Dual Fork Arm	Dual Fork Arm
Oculare	40 mm	40 mm	40 mm
Ingrandimento	51 x	59 x	70 x
Diagonale	1.25	1.25	1.25
Treppiede	Heavy Duty Steel Adjustable	Heavy Duty Steel Adjustable	Heavy Duty Steel Adjustable
CD ROM	NexRemote control software con cavo RS232	NexRemote control software con cavo RS232	NexRemote control software con cavo RS232
Alimentazione	Car battery adapter	Car battery adapter	Car battery adapter
Max. Ingrandimento	480 x	555 x	661 x
Min. Ingrandimento	29 x	34 x	40 x
Magnitudine limite	14	14.4	14.7
Trattamento	Starbright XLT Coating	Starbright XLT Coating	Starbright XLT Coating
Peso telescopio	19.05 kg	26.31	29.48 kg
Tipo motore	DC Servo motors with encoders, both axes	DC Servo motors with encoders, both axes	DC Servo motors with encoders, both axes
Risoluzione motore	0.14 arc seconds	0.14 arc seconds	0.14 arc seconds
Movimenti motori	Sidereal, Solar and Lunar	Sidereal, Solar and Lunar	Sidereal, Solar and Lunar
Movimenti montatura	Altazimuth, EQ North and EQ South	Altazimuth, EQ North and EQ South	Altazimuth, EQ North and EQ South
Procedura di allineamento	SkyAlign, Auto Two-Star Alignment, Two-star Align, SolarSystem Align, EQ North Align, EQ South Align, One-Star Align	SkyAlign, Auto Two-Star Alignment, Two-star Align, SolarSystem Align, EQ North Align, EQ South Align, One-Star Align	SkyAlign, Auto Two-Star Alignment, Two-star Align, SolarSystem Align, EQ North Align, EQ South Align, One-Star Align
PEC	Permanente program	Permanente program	Permanente program
Com. Porte	RS-232	RS-232	RS-232
MOTOR PORTS	Aux Port, Autoguide Ports	Aux Port, Autoguide Ports	Aux Port, Autoguide Ports
DATABASE	40,000+ objects, 100 user defined programmable objects. Enhanced information on over 200 objects	40,000+ objects, 100 user defined programmable objects. Enhanced information on over 200 objects	40,000+ objects, 100 user defined programmable objects. Enhanced information on over 200 objects
Alimentazione richiesta	12VDC 1.5A	12VDC 1.5A	12VDC 1.5A
GPS	Internal 16 channel	Internal 16 channel	Internal 16 channel